

Setting up Specific Generation Options

The generation options are arranged on two screens and are grouped into data fields and path definition.

The following topics are covered below:

- Invoking the Generation Options Setup Screens
- First Screen
- Second Screen

See also:

- XML Toolkit Features
- Using Natural Data Area as Data Source
- Using Document Type Definition as Data Source
- PF-Key Assignments

Invoking the Generation Options Setup Screens

► To invoke the first screen of the generation options function

- On the Main Menu screen, press PF10 **Optio(n)**.
The first screen of the Options setup function is displayed.
The map fields are described below.

First Screen

Special characters that are not valid in XML have to be converted into valid names. The following map enables you to change the default conversion settings, if required.

```

08:35:35          *** NATURAL XML Toolkit ***           2002-01-17
User DEFAULT      - Options -                         Library SYSEXXT

Additional fields
Counter separator character ..... @

XML name replacements
Namespace separator character ':' with .. $ 
Dot sign '.' with ..... / 

Natural variable name replacements
Plus sign '+' with ..... plus_____
Hash / Number sign '#' with ..... hash_____
Slash sign '/' with ..... slash_____
At sign '@' with ..... at_____
Paragraph sign '$' with ..... paragraph_____
Ampersand sign '&' with ..... ampersand_____
Dollar sign '$' with ..... dollar_____

Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12--
      Help        Exit          Next          Canc

```

Field Descriptions

Counter Separator Character

Belongs to Group:	Additional Fields
Format:	A1
Default Value:	@

Namespace Separator Character ":" with:

Belongs to Group:	XML Name Replacements
Format:	A1
Default Value:	\$

Dot Sign '.' with:

Belongs to Group:	XML Name Replacements
Format:	A1
Default Value:	/

Plus Sign '+' with:

Belongs to Group:	XML Variable Name Replacements
Format:	A11
Default Value:	plus

Hash / Number Sign '#' with:

Belongs to Group:	Natural Variable Name Replacements
Format:	A11
Default Value:	hash

Slash Sign '/' with:

Belongs to Group:	Natural Variable Name Replacements
Format:	A11
Default Value:	slash

At Sign '@' with:

Belongs to Group:	Natural Variable Name Replacements
Format:	A11
Default Value:	at

Paragraph Sign '§' with:

Belongs to Group:	Natural Variable Name Replacements
Format:	A11
Default Value:	para

Ampersand Sign '&' with:

Belongs to Group:	Natural Variable Name Replacements
Format:	A11
Default Value:	amp

Dollar Sign '\$' with:

Belongs to Group:	Natural Variable Name Replacements
Format:	A11
Default Value:	dollar

Second Screen

The second map of the Options function serves to define the location of the target or source DTD file used for the conversion.

► **To invoke the second screen of the Generation Options function**

- On the Main Menu screen, press PF10 **Optio(n)**.
- On the first screen, press PF8 **Next**.

The second screen of the Options function is displayed.

The map fields are described below.

```
08:36:10          *** NATURAL XML Toolkit ***          2002-01-17
User DEFAULT      - Options -          Library SYSEXXT

External file:
/nat_64/proj/natc/511/samples/sysexxt/*.dtd_____

Natural library:
SYSEXXT_


Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
Help          Exit          Prev          Canc
```

Field Descriptions

External File

Format:	A253
Default Value:	(Resource directory of current library)

Natural Library

Format:	A8
Default Value:	(current library)